

# TRIANGLE DOME With FLAT TOP, DIMPLE & FEET

Stable Forces per Batch Number

Excellent Tactile Effect

100% Traceability per Batch Number

Competitive Pricing

Superior Quality




Ideal for Mounting on Printed Circuit

Boards

Custom Options

Used in a multitude of Industries, such as:  
Membrane Switch, Automotive, Consumer  
Electronics, Medical, Appliance, etc

RoHS Compliant



Contact Configuration	SPST, Normally Open	Contact Resistance	<100 ohms
Contact Bounce (on)	<0.3ms	with Gold or Silver Plating	<1 ohm
Contact Bounce (off)	<6ms	Voltage/Current Maximum	12mA @ 24 Volts DC, RL
Operating Temperature	-55°C to 125°C	Breakdown Voltage	Over 200 Volts
Storage Temperature	-55°C to 125°C	Material	Stainless Steel Type 304
Humidity	0-97% (no condensation)	Life Expectancy	1 Million

Part No	Force	Size	Shape	Dimensions (mm)						
				Thickness	A	B	C	X	Y	Z
MD 8 - TDF - TOP - 400	400g	8mm	Triangle Flat Top with Dimple, with Feet	0.08	8.00	0.63	7.20	0.08	1.60	1.40
MD 9 - TDF - TOP - 400	400g	9mm	Triangle Flat Top with Dimple, with Feet	0.08	9.00	0.61	8.25	0.08	1.60	1.40
MD 10 - TDF - TOP - 320	320g	10mm	Triangle Flat Top with Dimple, with Feet	0.10	10.00	0.58	9.25	0.08	1.60	1.40
MD 10 - TDF - TOP - 400	400g	10mm	Triangle Flat Top with Dimple, with Feet	0.10	10.00	0.61	9.25	0.08	1.60	1.40
MD 12 - TDF - TOP - 400	400g	12mm	Triangle Flat Top with Dimple, with Feet	0.10	12.00	0.69	11.00	0.08	1.60	1.40

### MEMCON Limited

Compass House Vision Park Chivers Way HISTON  
Cambridge CB24 9AD United Kingdom  
T +44 1223 257724 F +44 1223 257800  
www.memcon.eu sales@memcon.eu

### MEMCON (Asia) Limited

Level 7 Parkview Centre  
7 Lau Li Street Causeway Bay Hong Kong  
T +852 3741 1411 F +852 3747 8980  
www.memcon.asia sales@memcon.asia